Forus Electric Pvt. Ltd.

12W LED Surface Panel Light DATASHEET

Forus Led Lights are energy efficient, brighter and has more life hours. They are used for indoor lighting application like Home lighting, office Lighting, Campus



| Lighting, Institution Lighting. | |
|---------------------------------------|-------------------------------------|
| TECHNICAL SPECIFICATION OF LED | |
| LED Type | SMD |
| LED Make | Seoul, Edison, Everlight |
| LED Efficacy | > 130 lm/W |
| Life Span | > 50,000 Hours |
| View Angle | 120 Degree |
| Color Rendering Index (CRI) | >80 |
| Color Temperature | 2700K - 6500K |
| TECHNICAL SPECIFICATION OF LED DRIVER | |
| Driver Efficiency | >87% |
| Driver Type | Constant Current |
| Input Operating Voltage | 140 - 270V AC |
| Total Harmonic Distortion | <20% |
| Surge Protection | Upto 2.5 kV |
| TECHNICAL SPECIFICATION OF LUMINAIRE | |
| Power Rating | 12W |
| Power Consumption | 12W ±10% |
| Operating Frequency | 50 Hz ± 3 Hz |
| Lumen Efficacy | >100 lm/W |
| Power Factor | >0.95 |
| Diffuser Type | Polycarbonate |
| Ingress Protection | IP20 or Better |
| Housing/Casing Material | Plastic Aluminium Pressure Die Cast |
| Housing Shape | Round |
| Housing Type | Surface |
| Diffuser Angle | 180 degree |
| Outer Diameter | 171 mm |
| Panel Housing height | 34 mm |
| Housing Driver Connection | Lock and Twist |
| Mounting Arrangement | Screw |
| | |